







MODEL	IMAGE	PARTICULAR
1 Mega Pixel Range of AHD Cameras		
HC-AHD-DM10N2C		•1MP 720P HIGH DEFINITION IMAGE SENSOR •25/30FPS @720P, 3.6MM Lens •IR Range of 20m with 24 IR LED.
HC-AHD-TM10N2C		•1MP 720P HIGH DEFINITION IMAGE SENSOR, •25/30FPS @ 720P, 3.6MM Lens, •IR Range of 20m with 24 IR LED, Plastic Housing.
HC-AHD-DM10N2E		•1/3" 1MP 720P HIGH DEFINITION IMAGE SENSOR •25/30FPS @ 720P, 3.6mm Lens •IR Range of 20m with 24 IR LED.
HC-AHD-TM10N2		•1/3" 1MP 720P HIGH DEFINITION IMAGE SENSOR, •25/30FPS @ 720P, 3.6mm Lens, •IR Range of 20m with 24 IR LED,IP 66 & Metal Housing.
HC-AHD-TM10N3		•1/3" 1MP 720P HIGH DEFINITION IMAGE SENSOR, •25/30FPS @ 720P, 3.6mm Lens, •IR Range of 30m with 36 IR LED, IP 66 & Metal Housing.
HC-AHD-TM10A6		•1/3" 1MP 720P HIGH DEFINITION IMAGE SENSOR •25/30FPS @ 720P,6/8mm Lens, •IR Range of 50m, with Two Power Array LED, IP 66 & Metal Housing
HC-AHD-TM10VFN6		•1/3" 1MP 720P HIGH DEFINITION IMAGE SENSOR •25/30FPS @ 720P, 2.8mm~12mm Varifocal Lens •IR Range of 60m, with 72 IR LED, IP 66 & Metal Housing
1.3 Mega Pixel Range of AHD Cameras		
HC-AHD-DM13N2		•1/3" 1.3MP 960P HIGH DEFINITION IMAGE SENSOR •25/30FPS @ 960P, 3.6MM Lens, •IR Range of 20m, with 24 IR LED.
HC-AHD-TM13N2		•1/3" 1.3MP 960P HIGH DEFINITION IMAGE SENSOR •25/30FPS @ 960P, 3.6MM Lens •IR Range of 20m, with 24 IR LED, IP 66 & Metal Housing.
HC-AHD-TM13N3		•1/3" 1.3MP 960P HIGH DEFINITION IMAGE SENSOR •25/30FPS @ 960P, 3.6MM Lens •IR Range of 30m, with 36 IR LED, IP 66 & Metal Housing.
HC-AHD-TS13N3		•1/2.8" 1.3MP SONY EXMOR IMAGE SENSOR, •25/30FPS @ 960P, 3.6/6mm Lens, •IR Range of 30m, with 36 IR LED, •IP 66 & Metal Housing.
HC-AHD-TS13A6		•1/2.8" 1.3MP SONY EXMOR IMAGE SENSOR •25/30FPS @ 960P, •6/8mm Lens, IR Range of 50m, with Two Power Array LED •IP 66 & Metal Housing.
HC-AHD-TS13VFN6		•1/2.8" 1.3MP SONY EXMOR IMAGE SENSOR, •25/30FPS @ 960P, 2.8~12mm Vari-focal Lens, •IR Range of 60m, with 72 IR LED, IP 66 & Metal Housing.
2 Mega Pixel Range of AHD Cameras		
HC-AHD-DS20N2		•1/2.8" 2MP SONY EXMOR IMAGE SENSOR •25/30FPS @ 1080P, 3.6MM Lens, •IR Range of 20m, with 24 IR LED.
HC-AHD-TS20N2		•1/2.8" 2MP SONY EXMOR IMAGE SENSOR, •25/30FPS @ 1080P, 3.6MM Lens, •IR Range of 20m, with 24 IR LED, IP 66 & Metal Housing.
HC-AHD-TS20N3		•1/2.8" 2MP SONY EXMOR IMAGE SENSOR •25/30FPS @ 1080P, 3.6/6mm Lens •IR Range of 30m, with 36 IR LED, IP 66 & Metal Housing.
HD AHD RECORDERS		
HD-AHD-404AN		•4ch. Video & 4ch. Audio, •1080N Realtime Playback •HDMI & VGA OUTPUT •Support 1 HDD upto 4TB, Mini 1U Casing, 2 USB 2.0
HD-AHD-804AN		•8ch. Video & 4ch. Audio, •1080N Channel Realtime Playback •HDMI & VGA OUTPUT •Support 1 HDD upto 4TB, Mini 1U Casing, 2 USB 2.0
HD-AHD-1602AN2		•16ch. Video & 4ch. Audio, •1080N Channel Realtime Playback •HDMI & VGA OUTPUT •Support 2 HDD upto 4TB each, Mini 1U Casing, 2 USB 2.0
HD-AHD-404AP		•4ch. Video & 4ch. Audio, •1080P Realtime Playback •HDMI & VGA OUTPUT •Support 1 HDD upto 4TB, Mini 1U Casing, 2 USB 2.0
HD-AHD-804AP		•8ch. Video & 4ch. Audio, •1080P Realtime Playback •HDMI & VGA OUTPUT •Support 1 HDD upto 4TB, Mini 1U Casing, 2 USB 2.0
HD-AHD-1602AP		•16ch. Video & 4ch. Audio, •1080P Realtime Playback •HDMI & VGA OUTPUT •Support 2 HDD upto 4TB each, Mini 1U Casing, 2 USB 2.0
HD-XVR-404AN		•4ch. Video & 4ch. Audio, •1080N Realtime Playback •HDMI & VGA OUTPUT •Support 1 HDD upto 4TB, Mini 1U Casing, 2 USB 2.0 •Support AHD/ CVI/ TVI/ CVBS & IP Camera
HD-XVR-804AN		•8ch. Video & 4ch. Audio, •1080N Channel Realtime Playback •HDMI & VGA OUTPUT •Support 1 HDD upto 4TB, Mini 1U Casing, 2 USB 2.0 •Support AHD/ CVI/ TVI/ CVBS & IP Camera
HD-XVR-1602AN		•16ch. Video & 4ch. Audio, •1080N Channel Realtime Playback •HDMI & VGA OUTPUT •Support 2 HDD upto 4TB each, Mini 1U Casing, 2 USB 2.0 •Support AHD/ CVI/ TVI/ CVBS & IP Camera
HD-XVR-3216AN	NEW HOUSING	•32ch. Video & 16ch. Audio, •1080N Channel Realtime Playback •HDMI & VGA OUTPUT •Support 4 HDD upto 4TB each, Mini 1U Casing, 2 USB 2.0 •Support AHD/ CVI/ TVI/ CVBS & IP Camera
HD-XVR-404AP		•4ch. Video & 4ch. Audio, •1080P Realtime Playback •HDMI & VGA OUTPUT •Support 1 HDD upto 4TB, Mini 1U Casing, 2 USB 2.0 •Support AHD/ CVI/ TVI/ CVBS & IP Camera
HD-XVR-804AP		•8ch. Video & 4ch. Audio, •1080P Realtime Playback •HDMI & VGA OUTPUT •Support 1 HDD upto 4TB, Mini 1U Casing, 2 USB 2.0 •Support AHD/ CVI/ TVI/ CVBS & IP Camera
HD-XVR-1602AP		•16ch. Video & 4ch. Audio, •1080P Realtime Playback •HDMI & VGA OUTPUT •Support 2 HDD upto 4TB each, Mini 1U Casing, 2 USB 2.0 •Support AHD/ CVI/ TVI/ CVBS & IP Camera
AHD SPEED DOME CAMERAS		
HC-AHD-SD1310A6		• 1/3" 1.3Mp Sony Exmor 10x Ultra-High Speed AHD Camera •25/30 fps @ 960P •IR Range upto 60m
HC-AHD-SD1330A10		• 1/3" 1.3Mp Sony Exmor 30x Ultra-High Speed AHD Camera •25/30 fps @ 960P •IR Range upto 100m

MODEL	IMAGE	PARTICULAR
1 Mega Pixel Range of CVI Cameras		
HC-CVI-DM10N2C		•1MP 720P High Definition Image Sensor •25/30FPS @720P, 3.6MM Lens •IR Range of 20m with 24 IR LED.
HC-CVI-TM10N2C		•1MP 720P High Definition Image Sensor, •25/30FPS @ 720P, 3.6MM Lens, •IR Range of 20m with 24 IR LED, Plastic Housing.
HC-CVI-D1000N2-W		•1/4" 1MP 720P High Definition Image Sensor, •25/30FPS @ 720P, 3.6MM Lens, •IR Range of 20m. With Smart IR.
HC-CVI-T1000N2-W		•1/4" 1MP 720P High Definition Image Sensor, •25/30FPS @ 720P, 3.6MM Lens, •IR Range of 20m with Smart IR, IP 66 Weather Proof
HC-CVI-D1100N2-W		•1/2.9" 1MP High Definition Image Sensor •25/30FPS @ 720P, 3.6mm Lens •IR Range of 20m with Smart IR.
HC-CVI-T1100N2-W		•1/2.9" 1MP High Definition Image Sensor •25/30FPS @ 720P, 3.6mm Lens •IR Range of 20m with Smart IR, IP 66 Weather Proof.
HD-CVI-D1100N2-SP		•1/2.9" 1MP High Definition Image Sensor •25/30FPS @ 720P, 3.6mm Lens •IR Range of 20m with Smart IR,
HD-CVI-T1100N2-SP		•1/2.9" 1MP High Definition Image Sensor •25/30FPS @ 720P, 3.6mm Lens •IR Range of 20m with Smart IR, IP 66 Weather Proof.
HD-CVI-T1100VFN4		•1/2.9" 1MP High Definition Image Sensor •25/30FPS @ 720P, 2.8~12mm Vari-Focal Lens •IR Range of 20m with Smart IR, IP 66 Weather Proof.
HC-CVI-D1100N2-P		•1/3" 1MP High Definition Image Sensor •25/30FPS @ 720P, 3.6mm Lens •IR Range of 20m with Smart IR.
HC-CVI-T1100N2-P		•1/3" 1MP High Definition Image Sensor •25/30FPS @ 720P, 3.6mm Lens •IR Range of 20m with Smart IR, IP 66 Weather Proof.
HC-CVI-T1100N2M-P		•1/3" 1MP High Definition Image Sensor •25/30FPS @ 720P, 3.6mm Lens •IR Range of 20m with Smart IR •IP 66 & Metal Housing.
HC-CVI-T1100BP		•1/2.9" 1MP High Definition Image Sensor •25/30FPS @ 720P, 3.6mm Lens •IR Range of 40m with Smart IR •IP 66 & Metal Housing.
HC-CVI-T1100DP		•1/2.9" 1MP High Definition Image Sensor •25/30FPS @ 720P, 3.6mm Lens •IR Range of 40m with Smart IR •IP 66 & Metal Housing.
1.3MP RANGE OF HDCVI CAMERAS		
HC-CVI-DM13N2		•1/2.9" 1.3MP High Definition Image Sensor •25/30FPS @ 960P, 3.6mm Lens •IR Range of 20m with 24 IR LEDs
HC-CVI-TM13N2		•1/2.9" 1.3MP High Definition Image Sensor •25/30FPS @ 960P, 3.6mm Lens •IR Range of 20m with 24 IR LEDs •IP 66 & Metal Housing.
HC-CVI-TM13N3		•1/2.9" 1.3MP High Definition Image Sensor •25/30FPS @ 960P, 3.6mm Lens •IR Range of 30m with 36 IR LEDs •IP 66 & Metal Housing.
HC-CVI-TM13N3		•1/2.9" 1.3MP High Definition Image Sensor •25/30FPS @ 960P, 6mm Lens •IR Range of 30m with 36 IR LEDs •IP 66 & Metal Housing.
HC-CVI-TM13N5		•1/2.9" 1.3MP High Definition Image Sensor •25/30FPS @ 960P, 6/8mm Lens •IR Range of 50m with Two Power Array LEDs •IP 66 & Metal Housing.
HC-CVI-TM13VFN6		•1/2.9" 1.3MP High Definition Image Sensor •25/30FPS @ 960P, 2.8~12mm Vari-Focal Lens •IR Range of 60m with 72 IR LEDs •IP 66 & Metal Housing.
2MP RANGE OF HDCVI CAMERAS		
HC-CVI-T2200N2-S		•1/2.8" 2MP High Definition Image Sensor •25/30FPS @ 1080P, 3.6mm Lens •IR Range of 20m with Smart IR •IP 66 & Plastic Housing.
HC-CVI-T2200BP		•1/2.8" 2MP High Definition Image Sensor •25/30FPS @ 1080P, 3.6mm Lens •IR Range of 20m with Smart IR •IP 66 & Metal Housing.
HC-CVI-D1200N2-MP	NO PIC	• 1/2.7" 2Megapixel CMOS • 25/30fps@1080P, 25/30/50/60fps@720P • 3.6mm fixed lens • Max. IR LEDs length 20m, Smart IR • IP67, DC12V
HC-CVI-T1200N2-SP		• 1/2.7" 2Megapixel CMOS • 25/30fps@1080P, 25/30/50/60fps@720P • 3.6mm fixed lens • Max. IR LEDs length 20m, Smart IR • IP67, DC12V
HC-CVI-T1200BP	NO PIC	• 1/2.7" 2Megapixel CMOS • 25/30fps@1080P • 6mm fixed lens • Max. IR LEDs length 50m, Smart IR • IP67, DC12V
HC-CVI-T1200DP	NO PIC	• 1/2.7" 2Megapixel CMOS • 25/30fps@1080P • 8mm fixed lens • Max. IR LEDs length 80m, Smart IR • IP67, DC12V
HC-CVI-T1200R-VF	NO PIC	• 1/2.7" 2Megapixel CMOS • 25/30fps@1080P • Day/Night(ICR), AWB, AGC, BLC, 2DNR • 2.7~12mm vari-focal lens • Max. IR LEDs length 30m, Smart IR, IP67, DC12V
2MP STARLIGHT RANGE OF HDCVI CAMERAS		
HC-CVI-D2200N2-SL		•1/2.8" 2MP sony Sensor •25/30FPS @ 1080P, 3.6mm Lens •IR Range of 20m with STARLIGHT
HC-CVI-T2200N3-SL		•1/2.8" 2MP Sony Sensor •25/30FPS @ 1080P, 3.6mm Lens •IR Range of 30m with STARLIGHT •IP 66 & Metal Housing.
HC-CVI-T2200DP-SL-0600		•1/2.8" 2MP Sony Sensor •25/30FPS @ 1080P, 6mm Lens •IR Range of 40m with STARLIGHT •IP 66 & Metal Housing.
HC-CVI-T2200DP-SL-0800		•1/2.8" 2MP Sony Sensor •25/30FPS @ 1080P, 8mm Lens •IR Range of 40m with STARLIGHT •IP 66 & Metal Housing.
HC-CVI-T2200VF4-SL		•1/2.8" 2MP Sony Sensor •25/30FPS @ 1080P, 2.8mm~12mm Lens •IR Range of 50m with STARLIGHT •IP 66 & Metal Housing.
HC-CVI-T2200VF6-SL		•1/2.8" 2MP Sony Sensor •25/30FPS @ 1080P, 5mm~50mm Lens •IR Range of 50m with STARLIGHT •IP 66 & Metal Housing.
2.4MP RANGE OF HDCVI CAMERAS		
HC-CVI-DS20N2		•1/2.8" 2.4MP SONY EXMOR IMAGE SENSOR •25/30FPS @ 1080P, 3.6MM Lens, •IR Range of 20m, with 24 IR LED.
HC-CVI-TS20N2P	NO PIC	•1/2.8" 2.4MP SONY EXMOR IMAGE SENSOR, •25/30FPS @ 1080P, 3.6MM Lens, •IR Range of 20m, with 24 IR LED & Plastic Housing.
HC-CVI-TS20N2		•1/2.8" 2.4MP SONY EXMOR IMAGE SENSOR, •25/30FPS @ 1080P, 3.6MM Lens, •IR Range of 20m, with 24 IR LED, IP 66 & Metal Housing.
HC-CVI-TS20N3		•1/2.8" 2.4MP SONY EXMOR IMAGE SENSOR •25/30FPS @ 1080P, 3.6/6mm Lens •IR Range of 30m, with 36 IR LED, IP 66 & Metal Housing.
HC-CVI-TS20N5		•1/2.8" 2.4MP SONY EXMOR IMAGE SENSOR •25/30FPS @ 1080P, 6/ 8mm Lens •IR Range of 30m, with Two Power Array LED •IP 66 & Metal Housing.
HC-CVI-TS20VFN6		•1/2.8" 2.4MP SONY EXMOR IMAGE SENSOR •25/30FPS @ 1080P, 2.8~12mm Vari-Focal Lens •IR Range of 30m, with Two Power Array LED •IP 66 & Metal Housing.
Elite Series HDCVI Recorders		
HD-CVR-4104S		•4ch. Video & 1ch. Audio, TRIBRID •720P Full Channel Realtime Playback •HDMI & VGA OUTPUT •Support 1 HDD upto 4TB, Mini 1U Casing, 2 USB 2.0
HD-CVR-4108S		•8ch. Video & 1ch. Audio, TRIBRID •720P Full Channel Realtime Playback •HDMI & VGA OUTPUT •Support 1 HDD upto 4TB, Mini 1U Casing, 2 USB 2.0
HD-CVR-4116S		•16ch. Video & 1ch. Audio, TRIBRID •720P Full Channel Realtime Playback •HDMI & VGA OUTPUT •Support 1 HDD upto 4TB, Mini 1U Casing, 2 USB 2.0
HD-CVR-4216S		•16ch. Video & 1ch. Audio, TRIBRID •720P Full Channel Realtime Playback •HDMI & VGA OUTPUT •Support 2 HDD upto 4TB each, 1U Casing, 2 USB 2.0
HD-CVR-5204S-A		•4ch. Video & 4ch. Audio, TRIBRID •1080P Full Channel Playback •HDMI & VGA OUTPUT, Alarm output •Support 2 HDD upto 4TB each, 1U Casing, 2 USB 2.0
HD-CVR-5208S-A		•8ch. Video & 4ch. Audio, TRIBRID •1080P Full Channel Playback •HDMI & VGA OUTPUT, Alarm output •Support 2 HDD upto 4TB each, 1U Casing, 2 USB 2.0
HD-CVR-5216S-A		•16ch. Video & 4ch. Audio, TRIBRID •1080P Full Channel Playback •HDMI & VGA OUTPUT, Alarm output •Support 2 HDD upto 4TB each, 1U Casing, 2 USB 2.0
HD-CVR-4224S		•24ch. Video & 1ch. Audio, TRIBRID •720P Full Channel Realtime Playback •HDMI,AV & VGA OUTPUT •Support 2 HDD upto 4TB each, 1U Casing, 2 USB 2.0
HD-CVR-4232S		•32ch. Video & 1ch. Audio, TRIBRID •720P Full Channel Realtime Playback •HDMI,AV & VGA OUTPUT •Support 2 HDD upto 4TB each, 1U Casing, 2 USB 2.0
HD-CVR-5432S	NO PIC	•32ch. Video & 4ch. Audio, TRIBRID •1080P Non-Realtime Recording •2 HDMI,AV & VGA OUTPUT, Alarm Output •Support 4 HDD upto 16TB, 1.5U Casing, 3 USB 2.0 •eSATA support, Mic IN & OUT
PREMIUM SERIES HDCVI RECORDERS		
HD-CVR-4104C1		•4ch. Video & 1ch. Audio, TRIBRID •720P Full Channel Realtime Playback •HDMI & VGA OUTPUT •Support 1 HDD upto 4TB, Mini 1U Casing, 2 USB 2.0
HD-CVR-4108C1		•8ch. Video & 1ch. Audio, TRIBRID •720P Full Channel Realtime Playback •HDMI & VGA OUTPUT •Support 1 HDD upto 4TB, Mini 1U Casing, 2 USB 2.0
HD-CVR-4104H1		•4ch. Video & 1ch. Audio, TRIBRID •720P Full Channel Realtime Playback •HDMI & VGA OUTPUT •Support 1 HDD upto 4TB, Mini 1U Casing, 2 USB 2.0
HD-CVR-4104H1-A		•4ch. Video & 4ch. Audio, TRIBRID •720P Full Channel Realtime Playback •HDMI & VGA OUTPUT, Alarm Output •Support 1 HDD upto 4TB, 1U Casing, 2 USB 2.0
HD-CVR-4108H1		•8ch. Video & 1ch. Audio, TRIBRID •720P Full Channel Realtime Playback •HDMI & VGA OUTPUT •Support 1 HDD upto 4TB, Mini 1U Casing, 2 USB 2.0
HD-CVR-4116H1		16ch. Video & 1ch. Audio, TRIBRID •720P Full Channel Realtime Playback •HDMI & VGA OUTPUT •Support 1 HDD upto 4TB, Mini 1U Casing, 2 USB 2.0
HD-CVR-4216H2		•16ch. Video & 1ch. Audio, TRIBRID •720P Full Channel Realtime Playback •HDMI & VGA OUTPUT •Support 2 HDD upto 4TB each, 1U Casing, 2 USB 2.0
HD-CVR-4232H2		•32ch. Video & 1ch. Audio, TRIBRID •720P Full Channel Realtime Playback •HDMI,AV & VGA OUTPUT •Support 2 HDD upto 4TB each, 1U Casing, 2 USB 2.0
HD-CVR-5416H4		•16ch. Video & 4ch. Audio, TRIBRID •1080P Non-Realtime Recording •HDMI,AV & VGA OUTPUT •Support 4 HDD upto 16TB, 1.5U Casing, 2 USB 2.0
HD-CVR-5816H8-V2		•16ch. Video & 16ch. Audio, TRIBRID •1080P Non-Realtime Recording •2 HDMI,AV & VGA OUTPUT, Alarm Output •Support 8 HDD upto 32TB, 2U Casing, 2 USB 2.0
HD-CVR-5432H4-S2		•32ch. Video & 4ch. Audio, TRIBRID •1080P Non-Realtime Recording •2 HDMI,AV & VGA OUTPUT, Alarm Output •Support 4 HDD upto 16TB, 1.5U Casing, 2 USB 2.0
HD-CVR-5832H8-S2		•32ch. Video & 16ch. Audio, TRIBRID •1080P Non-Realtime Recording •2 HDMI,AV & VGA OUTPUT, Alarm Output •Support 8 HDD upto 32TB, 2U Casing, 2 USB 2.0
PREMIUM N SERIES HDCVI RECORDERS		
HD-CVR-4104H1-S3		• 4Channel, Support HDCVI/Analog/IP Video input • H.264+/H.264 dual-stream video compression • All channel 1080N/720P recording • ONVIF Version 2.4.1 conformance • Support 1 SATA HDD up to 6TB, 2 USB2.0
HD-CVR-4108H1-S3		• 8Channel, Support HDCVI/Analog/IP Video input • H.264+/H.264 dual-stream video compression • All channel 1080N/720P recording • ONVIF Version 2.4.1 conformance • Support 1 SATA HDD up to 6TB, 2 USB2.0
HD-CVR-4116H1-S3		• 16Channel, Support HDCVI/Analog/IP Video input • H.264+/H.264 dual-stream video compression • All channel 1080N/720P recording • ONVIF Version 2.4.1 conformance • Support 1 SATA HDD up to 6TB, 2 USB2.0
HD-CVR-4216H2-S3		• 16Channel, Support HDCVI/Analog/IP Video input • H.264+/H.264 dual-stream video compression • All channel 1080N/720P recording • ONVIF Version 2.4.1 conformance • Support 2 SATA HDD up to 12TB, 2 USB2.0
HD-CVR-5108H1-S3		• 8Channel, Support HDCVI/Analog/IP Video input • H.264+/H.264 dual-stream video compression • All channel 1080N/720P realtime or 1080P non-realtime recording, ONVIF Version 2.4.1 conformance. • Support 1 SATA HDD up to 6TB, 2 USB2.0
HD-CVR-5216H2-S3		• 16Channel, Support HDCVI/Analog/IP Video input • H.264+/H.264 dual-stream video compression • All channel 1080N/720P realtime or 1080P non-realtime recording, ONVIF Version 2.4.1 conformance. • Support 2 SATA HDD up to 12TB, 1 USB2.0, 1 USB3.0
HDCVI SPEED DOME CAMERAS		
HC-CVI-SD1310A6		• 1/3" 1.3Mp Sony Exmor 10x Ultra-High Speed HDCVI Camera •25/30 fps @ 960P •IR Range upto 60m
HC-CVI-SD1330A10		• 1/3" 1.3Mp Sony Exmor 30x Ultra-High Speed HDCVI Camera •25/30 fps @ 960P •IR Range upto 100m
HC-CVI-SD120A10-H		• 1/3" 1.3Mp Sony Exmor 30x Ultra-High Speed HDCVI Camera •Max 50/60fps@720P resolution •IR Range upto 100m •Built-in 2/1 alarm in/out

MODEL	IMAGE	PARTICULAR
RAPID SERIES NETWORK CAMERAS		
HC-IPC-D4130VP	NO PIC	• 1/3" 1.3 Mega Pixel Sony Exmor Sensor •25/30FPS@960P (1280X960), H.264&MJPEG Encoding •IR Range of 30m, with Smart IR & POE. •Multiple Network Monitoring, Web Viewer, CMS(Hifocus RAPID).
HC-IPC-T4130VP		• 1/3" 1.3 Mega Pixel Sony Exmor Sensor •25/30FPS@960P (1280X960), H.264&MJPEG Encoding •3.6/6mm Lens, IR Range of 30m, & POE. •Multiple Network Monitoring, Web Viewer, CMS(Hifocus RAPID). •IP67 & Weather Proof Housing.
HC-IPC-D4220VP	NO PIC	• 1/3" 2 Mega Pixel Sony Exmor Sensor •25/30FPS@1080P (1920x1080), H.264&MJPEG Encoding •IR Range of 30m, & POE. •Multiple Network Monitoring, Web Viewer, CMS(Hifocus RAPID).
HC-IPC-T4220VP		• 1/3" 2 Mega Pixel Sony Exmor Sensor •25/30FPS@1080P (1920x1080), H.264&MJPEG Encoding •3.6/6mm Lens, IR Range of 30m, & POE. •Multiple Network Monitoring, Web Viewer, CMS(Hifocus RAPID). •IP67 & Weather Proof Housing.
HC-IPC-T4220VP-VF		• 1/3" 2 Mega Pixel Sony Exmor Sensor •25/30FPS@1080P (1920x1080), H.264&MJPEG Encoding •2.8~12mm Varif-focal Lens, IR Range of 50m & POE. •Multiple Network Monitoring, Web Viewer, CMS(Hifocus RAPID). •IP67 & Weather Proof Housing.
HC-IPC-D4440K-VP		• 1/3" 4 Mega Pixel Progressive Scan CMOS •20FPS@4MP (2560x1440), H.265, H.264 & MJPEG Encoding •IR Range of 20m, & POE. •Multiple Network Monitoring, Web Viewer, CMS(Hifocus RAPID).
HC-IPC-T4440K-VP		• 1/3" 4 Mega Pixel Progressive Scan CMOS •20FPS@4MP (2560x1440), H.265, H.264 & MJPEG Encoding •3.6/6mm Lens, IR Range of 30m, & POE. •Multiple Network Monitoring, Web Viewer, CMS(Hifocus RAPID). •IP67 & Weather Proof Housing.
HC-IPC-T4440K-VP-VF		• 1/3" 4 Mega Pixel Progressive Scan CMOS •20FPS@4MP (2560x1440), H.265, H.264 & MJPEG Encoding •2.8~12mm Vari-focal Lens, IR Range of 50m, & POE. •Multiple Network Monitoring, Web Viewer, CMS(Hifocus RAPID). •IP67 & Weather Proof Housing.
HC-IPC-D1300N2		• 1/3" 1.3 Mega Pixel Progressive Scan CMOS •25/30FPS@960P (1280X960), H.264&MJPEG Encoding •IR Range of 20m, with Smart IR & POE. •Multiple Network Monitoring, Web Viewer, CMS (Smart PSS & DSS) & DMSS
HC-IPC-T1300N2		• 1/3" 1.3 Mega Pixel Progressive Scan CMOS •25/30FPS@960P (1280X960), H.264&MJPEG Encoding •3.6/6mm Lens, IR Range of 30m with Smart IR & POE. •Multiple Network Monitoring, Web Viewer, CMS (Smart PSS & DSS) & DMSS •IP67 & Weather Proof Housing.
HC-IPC-D2200N2		• 1/3" 2 Mega Pixel Progressive Scan CMOS •25/30FPS@1080P (1920X1080P), H.264&MJPEG Encoding •IR Range of 20m, with Smart IR & POE. •Multiple Network Monitoring, Web Viewer, CMS (Smart PSS & DSS) & DMSS
HC-IPC-T2200N2		• 1/3" 2 Mega Pixel Progressive Scan CMOS •25/30FPS@1080P (1920X960), H.264&MJPEG Encoding •3.6/6mm Lens, IR Range of 30m with Smart IR & POE. •Multiple Network Monitoring, Web Viewer, CMS (Smart PSS & DSS) & DMSS •IP67 & Weather Proof Housing.
HC-IPC-D3300N2		• 1/3" 3 Mega Pixel Progressive Scan CMOS •20FPS@3MP (2048x1536), H.264&MJPEG Encoding •IR Range of 20m, with Smart IR & POE. •Multiple Network Monitoring, Web Viewer, CMS (Smart PSS & DSS) & DMSS
HC-IPC-T3300N2		• 1/3" 3 Mega Pixel Progressive Scan CMOS •20FPS@3MP (2048X1536), H.264&MJPEG Encoding •3.6/6mm Lens, IR Range of 30m with Smart IR & POE. •Multiple Network Monitoring, Web Viewer, CMS (Smart PSS & DSS) & DMSS •IP67 & Weather Proof Housing.
HC-IPC-T3300MVFN4		• 1/3" 3 Mega Pixel Progressive Scan CMOS •20FPS@3MP (2048X1536), H.264&MJPEG Encoding •2.8~12mm Motorized Vari-Focal Lens, IR Range of 40m with Smart IR & POE. SD card Support. •Multiple Network Monitoring, Web Viewer, CMS (Smart PSS & DSS) & DMSS •IP67 & Weather Proof Housing.
HC-IPC-EB4400	NO PIC	• 1/3"4Megapixel progressive scan CMOS • Max 15fps@4M(2592×1520), 25/30fps@1080P • Day/Night(Electronic), 3DNR, AWB,AGC,BLC • 1.18mm fixed lens • Micro SD memory, IK10, PoE
RAPID SERIES NETWORK VIDEO RECORDERS		
HD-NVR-4104VP		•4ch with 1080p Real-time Live Preview •Max 32Mbps incoming bandwidth •ONVIF Version 2.4 conformance •Support 1 SATA HDD up to 6TB, 2 USB2.0 •Multiple network monitoring: Web viewer, CMS(Hifocus RAPID)
HD-NVR-4108VP		•8ch with 1080p Real-time Live Preview •Max 48Mbps incoming bandwidth •ONVIF Version 2.4 conformance •Support 1 SATA HDD up to 6TB, 2 USB2.0 •Multiple network monitoring: Web viewer, CMS(Hifocus RAPID).
HD-NVR-4216VP		•16ch with 1080p Real-time Live Preview •Max 160Mbps incoming bandwidth •ONVIF Version 2.4 conformance •Support 2 SATA HDD up to 12TB, 2 USB2.0 •Multiple network monitoring: Web viewer, CMS(Hifocus RAPID). •1ch. Face Detection/1ch. Perimeter Intrusion
HD-NVR-4232VP		•32ch with 1080p Real-time Live Preview •Max 200Mbps incoming bandwidth •ONVIF Version 2.4 conformance •Support 2 SATA HDD up to 12TB, 2 USB2.0 •Multiple network monitoring: Web viewer, CMS(Hifocus RAPID).
HD-NVR-4832VP	NO PIC	•32ch with 1080p Real-time Live Preview •Max 200Mbps incoming bandwidth •ONVIF Version 2.4 conformance •Support 8 SATA HDD up to 6TB each, 2 USB2.0 •Multiple network monitoring: Web viewer, CMS(Hifocus RAPID).
PREMIUM SERIES NETWORK VIDEO RECORDER		
HD-NVR-4104H1		•4ch with 1080p Real-time Live Preview •Max 80Mbps incoming bandwidth •ONVIF Version 2.4 conformance •Support 1 SATA HDD up to 4TB, 2 USB2.0 •Multiple network monitoring: Web viewer, CMS(DSS/Smart PSS) & DMSS
HD-NVR-4108H1		•8ch with 1080p Real-time Live Preview •Max 80Mbps incoming bandwidth •ONVIF Version 2.4 conformance •Support 1 SATA HDD up to 4TB, 2 USB2.0 •Multiple network monitoring: Web viewer, CMS(DSS/Smart PSS) & DMSS
HD-NVR-4216H2		•16ch with 1080p Real-time Live Preview •Max 200Mbps incoming bandwidth •ONVIF Version 2.4 conformance •Support 2 SATA HDD up to 8TB, 2 USB2.0 •Multiple network monitoring: Web viewer, CMS(DSS/Smart PSS) & DMSS
HD-NVR4416H4		•16ch with 1080p Real-time Live Preview •Max 200Mbps incoming bandwidth •ONVIF Version 2.4 conformance •Support 4 SATA HDD up to 16TB, 2 USB2.0 •Multiple network monitoring: Web viewer, CMS(DSS/Smart PSS) & DMSS
HD-NVR-4232H2		•32ch with 1080p Real-time Live Preview •Max 200Mbps incoming bandwidth •ONVIF Version 2.4 conformance •Support 2 SATA HDD up to 8TB, 2 USB2.0 •Multiple network monitoring: Web viewer, CMS(DSS/Smart PSS) & DMSS
HD-NVR7864H8	NO PIC	•64ch with 1080p Real-time Live Preview •Max 256Mbps incoming bandwidth •ONVIF Version 2.3 conformance •Support 8 SATA HDDs up to 32TB, 4 USB2.0, 1 eSATA. •Multiple network monitoring: Web viewer, CMS(DSS/Smart PSS) & DMSS
HD-NVR4416H4-K		• 16Ch with 1080p Real-Time Live Preview • H.265/H.264/MJPEG dual codec decoding • Max 256Mbps incoming bandwidth • Up to 8ch@1080P(4ch@H.265+4ch@H.264) realtime live-view; ONVIF Version 2.4 conformance • 2HDMI/1 VGA simultaneous video output • Support 4 SATA HDDs up to 24TB, 3 USB(2 USB3.0), 1 eSATA port
HD-NVR4232H2-K		• 16Ch with 1080p Real-Time Live Preview • H.265/H.264/MJPEG dual codec decoding • Max 256Mbps incoming bandwidth • Up to 8ch@1080P(4ch@H.265+4ch@H.264) realtime live-view; ONVIF Version 2.4 conformance • 2HDMI/1 VGA simultaneous video output • Support 2 SATA HDDs up to 12TB, 2 USB(1 USB3.0)
HD-NVR4432H4-K		• 32Ch with 1080p Real-Time Live Preview • H.265/H.264/MJPEG dual codec decoding • Max 256Mbps incoming bandwidth • Up to 8ch@1080P(4ch@H.265+4ch@H.264) realtime live-view; ONVIF Version 2.4 conformance • 2HDMI/1 VGA simultaneous video output • Support 4 SATA HDDs up to 24TB, 3 USB(2 USB3.0), 1 eSATA port
HD-NVR4832H8-K		• 32Ch with 1080p Real-Time Live Preview • H.265/H.264/MJPEG dual codec decoding • Max 256Mbps incoming bandwidth • Support 8 SATA HDDs up to 48TB, 4 USB(2 USB3.0), 1 eSATA port • 2HDMI/1 VGA simultaneous video output
NETWORK SPEED DOME CAMERAS		
HC-IPC-SD2013-H		• 1/3" 1.3Mp 20X Ultra High Speed Network PTZ •25/30 fps @ 1.3MP (1280X960) •Built-in 2/1 alarm in/out •Micro SD memory, IP66
HC-IPC-SD2013A10-H		• 1/3" 1.3Mp 20X Ultra High Speed Network PTZ •25/30 fps @ 1.3MP (1280X960) •Built-in 2/1 alarm in/out •Micro SD memory, IP66 •IR Range upto 100m
HC-IPC-SD2020A10-H		• 1/3" 2Mp 20X Ultra High Speed Network PTZ •25/30 fps @ 1080P (1920x1080) •Built-in 2/1 alarm in/out •Micro SD memory, IP66 •IR Range upto 100m
HC-IPC-SD3020A10-H		• 1/3" 2Mp 30X Ultra High Speed Network PTZ •25/30 fps @ 1080P (1920x1080) •Built-in 2/1 alarm in/out •Micro SD memory, IP66 •IR Range upto 100m

MODEL	IMAGE	PARTICULAR
HF-R5		• 2.8" TFT True Color LCD • Fingerprint, Password & RFID Card • Max. 500 Fingerprint Records • Data Exports directly to USB Drive in Excel Format
HF-R52		• 2.4" TFT True Color LCD • Fingerprint, Password & RFID Card • Max. 1000 Fingerprint Records • RS485, USB Drive/Link & TCP/IP are the Interface Ports for Data Transfer. • Battery Back up for 2-3 Hours. • Access Control (Optional)
HF-R60		• 2.4" TFT True Color LCD • Fingerprint, Password & RFID Card • Max. 3000 Fingerprint Records • RS485, USB Drive/Link & TCP/IP are the Interface Ports for Data Transfer. • Battery Back Up (Optional) • Access Control (Optional)
HF-R302F		• 2.8" TFT True Color LCD • Face Recognition, Fingerprint, Password & RFID Card • Max. 3000 Fingerprint Records & 500 Face Storage. • RS485, USB Drive/Link & TCP/IP are the Interface Ports for Data Transfer. • Battery Back Up (Optional) • Access Control (Optional)

S.NO.	PICTURE	MODEL	SPECIFICATION
VILLA SYSTEM VIDEO DOOR PHONE			
1		HF-FNP-4	*4.3" TFT color screen with low power consumption, no radiation with high definition. *Intercommunication between indoor unit and outdoor unit. *Hands-free intercommunication. *Monitoring the outdoor. *Smart unlocking door option. *Brightness, chroma and ring adjustable. *8-chord melody rings for option. *DIY installation. *Gain control: Automatic
2		HF-SNP-7	*7" TFT color screen with low power consumption, no radiation with high definition. *Connect an external CCTV camera. *Intercommunication between indoor unit and outdoor unit. *Hands-free intercommunication with feather touch keys. *Monitoring the outdoor. *Smart unlocking door option. *Brightness, chroma and ring adjustable. *8-chord melody rings for option. *DIY installation. *Gain control: Automatic
3		HF-SMP-7	*7" TFT color screen with low power consumption, no radiation with high definition. *2GB memory card, video/ snapshot recording function. *Intercommunication between indoor unit and outdoor unit. *Hands-free intercommunication with feather touch keys. *Monitoring the outdoor. *Smart unlocking door option. *Brightness, chroma and ring adjustable. *8-chord melody rings for option. *DIY installation. *Gain control: Automatic
4		HF-9680	*8.3" TFT color screen with low power consumption, no radiation with high definition. *Intercommunication between indoor unit and outdoor unit. *Hands-free intercommunication with feather touch keys. *Monitoring the outdoor. *Smart unlocking door with RFID access. *Brightness, chroma and ring adjustable. *8-chord melody rings for option. *DIY installation. *Gain control: Automatic
5		HF-37M2	*7" TFT color screen with low power consumption, no radiation with high definition. *Connect an external CCTV camera. *Intercommunication between indoor unit and outdoor unit. *Hands-free intercommunication with feather touch keys. *Monitoring the outdoor with two different area. *Smart unlocking door option with two different location. *Brightness, chroma and ring adjustable. *8-chord melody rings for option. *DIY installation. *Gain control: Automatic
6		HF-37T2	*7" TFT color screen with low power consumption, no radiation with high definition. *Two Indoor Unit & One Outdoor Unit *Connect an external CCTV camera in each Indoor Unit. *Intercommunication between indoor unit and outdoor unit. *Hands-free intercommunication with feather touch keys. *Monitoring the outdoor. *Smart unlocking door option. *Brightness, chroma and ring adjustable. *8-chord melody rings for option. *DIY installation. *Gain control: Automatic
7		HF-37T4	*7" TFT color screen with low power consumption, no radiation with high definition. *Four Indoor Unit & One Outdoor Unit *Connect an external CCTV camera in each Indoor Unit. *Intercommunication between indoor unit and outdoor unit. *Hands-free intercommunication with feather touch keys. *Monitoring the outdoor. *Smart unlocking door option. *Brightness, chroma and ring adjustable. *8-chord melody rings for option. *DIY installation. *Gain control: Automatic
8		HF-97T2	*7" TFT color screen with low power consumption, no radiation with high definition. *Two Indoor Unit with photo/ video recording & One Outdoor Unit *2GB Memory card for photo/ video storage. *Intercommunication between indoor unit and outdoor unit. *Hands-free intercommunication with feather touch keys. *Monitoring the outdoor. *Smart unlocking door option. *Brightness, chroma and ring adjustable. *8-chord melody rings for option. *DIY installation. *Gain control: Automatic
9		HF-97T4	*7" TFT color screen with low power consumption, no radiation with high definition. *Four Indoor Unit with photo/ video recording & One Outdoor Unit *2GB Memory card for photo/ video storage. *Intercommunication between indoor unit and outdoor unit. *Hands-free intercommunication with feather touch keys. *Monitoring the outdoor. *Smart unlocking door option. *Brightness, chroma and ring adjustable. *8-chord melody rings for option. *DIY installation. *Gain control: Automatic
MULTI APARTMENT VIDEO DOOR PHONE			
10		HF-4VCR	*Outdoor station unit with respective keys to each apartment. *Connect various size of screen inches till four Indoor units *Inbuilt colour camera with infrared. *RFID access control inbuilt.
11		HF-8VCR	*Outdoor station unit with respective keys to each apartment. *Connect various size of screen inches till eight Indoor units *Inbuilt colour camera with infrared. *RFID access control inbuilt.
12		HF-12VCR	*Outdoor station unit with respective keys to each apartment. *Connect various size of screen inches till twelve Indoor units *Inbuilt colour camera with infrared. *RFID access control inbuilt.
13		HF-28T4	*Outdoor station unit with respective keys to each apartment. *Connect various size of screen inches till four Indoor units *Inbuilt colour camera with infrared. *RFID access control inbuilt.
14		HF-820VCR	*Outdoor station unit with respective keys to each apartment. *Connect various size of screen inches upto 9999 Indoor units *Inbuilt colour camera with infrared. *RFID access control inbuilt.
15		HF-TFT2700	*7" TFT color screen with low power consumption, no radiation with high definition. *Intercommunication between indoor unit and outdoor unit. *Hands-free intercommunication with feather touch keys. *Monitoring the outdoor. *Smart unlocking door option. *Brightness, chroma and ring adjustable. *8-chord melody rings for option.
16		HF-TFT53	*4.3" TFT color screen with low power consumption, no radiation with high definition. *Intercommunication between indoor unit and outdoor unit. *Hands-free intercommunication with feather touch keys. *Monitoring the outdoor. *Smart unlocking door option. *Brightness, chroma and ring adjustable. *8-chord melody rings for option.
17		HF-PS18	*Input power AC220V/50HZ, the output voltage DC18V, door machine with a single power supply separately *Required power supply for each two decoder(HF-980H4) device.
18		HF-980H4	*Decoder can connect 4 indoor units. *Intermediate between indoor unit and outdoor unit.

MODEL	PRODUCT PICTURE	PARTICULAR
HF-S04-60W		•1-4 port:Default:10/100Mbps •CCTV Mode:10Mbps; UPLINK:100Mbps •IEEE 802.3/802.3u/802.3af/at •Backplane Bandwidth 1G •Additional 2 Uplink ports •On Surveillance mode support 250m distance.
HF-S08-120W		•1-8 port:Default:10/100Mbps •CCTV Mode:10Mbps; UPLINK:100Mbps •IEEE 802.3/802.3u/802.3af/at •Backplane Bandwidth 1.8G •Additional 1 Uplink ports •On Surveillance mode support 250m distance.
HF-SG08-120W		•1-8 port:Default:10/100Mbps •CCTV Mode:10Mbps; UPLINK:1000Mbps •IEEE 802.3/802.3u/802.3af/at •Backplane Bandwidth 7G •Additional 2 Uplink ports •On Surveillance mode support 250m distance.
HF-SG16-300W		•16×RJ45,PoE+ 10/100Base-TX •2*10/100/1000Base-T+1*1000Base-X(combo) •IEEE 802.3,IEEE 802.3u,IEEE 802.3 ab •Exchange Capacity 7.2Gbps •Single Port PoE Power Output 30W, Voltage 54VDC •Web Management Port & SPF Port
HF-SG24-420W		•24×RJ45,PoE+ 10/100Base-TX •2*10/100/1000Base-T+1*1000Base-X(combo) •IEEE 802.3,IEEE 802.3u,IEEE 802.3 ab •Exchange Capacity 8.8Gbps •Single Port PoE Power Output 30W, Voltage 54VDC •Web Management Port & SPF port
HF-SGG24-420W		•24×RJ45,PoE+ 10/100/1000Base-TX •2*1000Mbps SFP Port and 2*10/100/1000Base-T •IEEE 802.3,IEEE 802.3u,IEEE 802.3 ab •Exchange Capacity 56Gbps •Single Port PoE Power Output 30W, Voltage 54VDC •Web Management Port
HF-P100R		•PoE IN & PoE Out: 100Mbps •Supports IEEE802.3af, IEEE802.3at standards •Transmission distance upto 400m by cascading number of repeaters

MODEL	PRODUCT PICTURE	PARTICULAR
SP-104		•4Channel Power Supply •Individual Port supply 1A •Input 240v AC, Oupur 12V DC •Filtered & Electronically regulated output
SP-108		•8Channel Power Supply •Individual Port supply 1A •Input 240v AC, Oupur 12V DC •Filtered & Electronically regulated output
SP-116		•16Channel Power Supply •Individual Port supply 1A •Input 240v AC, Oupur 12V DC •Filtered & Electronically regulated output
SP-1205		•12v 5a Power Supply •Thermal Shutdown •Over Load Protection •Short Circuit Protection
SP-1210		•12v 10a Power Supply •Thermal Shutdown •Over Load Protection •Short Circuit Protection